



ELASTOMERIC ROOFING SYSTEMS

COATING REQUIREMENTS

gallons per 100 square feet

CATEGORY		SYSTEM	Average Dry Film Thickness	COATING REQUIREMENTS				
				AF-130	AF-130BC	AF-130FR	AF-130MB	AF-130XT
ARS-1	FULLY REINFORCED SYSTEMS for ASPHALT ROOFS	ARS-1A	45	2	3			
		ARS-1A(50XT)	50		3			3
	FULLY REINFORCED SYSTEMS for CONCRETE ROOFS	ARS-1C	45	2	3			
		ARS-1C(50XT)	50		3			3
	FULLY REINFORCED SYSTEMS for SINGLE-PLY ROOFS	ARS-1SP	45					
		ARS-1SP(50XT)	50		3			3
FM APPROVED SYSTEM	ARS-1FR	45			5			
ARS-2	PARTIALLY REINFORCED SYSTEMS for ASPHALT ROOFS	ARS-2 (A25)	25	1.5	1.5			
		ARS-2 (A30XT)	30	1.25	1.25			1.25
	PARTIALLY REINFORCED SYSTEMS for CONCRETE ROOFS	ARS-2 (C25)	25	1.5	1.5			
		ARS-2 (C30XT)	30	1.25	1.25			1.25
	PARTIALLY REINFORCED SYSTEMS for METAL ROOFS	ARS-2 (M15)	15	1	1			
		ARS-2 (M20)	20	1.25	1.25			
		ARS-2 (M25XT)	25	1	1			1
	PARTIALLY REINFORCED SYSTEMS for SINGLE-PLY ROOFS	ARS-2 (SP20XT)	20		1.25			1.25
ARS-2 (SP30XT)		30		1.25			2.5	
ARS-3	COATING ONLY SYSTEMS	ARS-3 (15)	15	1	1			
		ARS-3 (20)	20	1.25	1.25			
		ARS-3 (15MB)	15				2	