



ELASTOMERIC ROOFING SYSTEMS

Recommended Uses & Warranty

| CATEGORY | | SPECIFICATION # | SUBSTRATE | | | | | | WARRANTY | |
|--------------------|---|-----------------|-----------|------------|----------------|--------------------|------------|----------|----------|--------|
| | | | Metal | Smooth BUR | Smooth Mod-Bit | Granulated Asphalt | Single-ply | Concrete | Material | System |
| ARS-1 | FULLY REINFORCED SYSTEMS for ASPHALT ROOFS | ARS-1A | | X | X | X | | | 10 | 10 |
| | | ARS-1A(50XT) | | X | X | X | | | 15 | 15 |
| | FULLY REINFORCED SYSTEMS for CONCRETE ROOFS | ARS-1C | | | | | | X | 10 | 10 |
| | | ARS-1C(50XT) | | | | | | X | 15 | 15 |
| | FULLY REINFORCED SYSTEMS for SINGLE-PLY ROOFS | ARS-1SP | | | | | X | | 10 | 10 |
| | | ARS-1SP(50XT) | | | | | X | | 15 | 15 |
| FM APPROVED SYSTEM | ARS-1FR | | X | X | X | | | 10 | 10 | |
| ARS-2 | PARTIALLY REINFORCED SYSTEMS for ASPHALT ROOFS | ARS-2 (A25) | | X | X | X | | | 5 | NA |
| | | ARS-2 (A30XT) | | X | X | X | | | 10 | 5 |
| | PARTIALLY REINFORCED SYSTEMS for CONCRETE ROOFS | ARS-2 (C25) | | | | | | X | 5 | NA |
| | | ARS-2 (C30XT) | | | | | | X | 10 | 5 |
| | PARTIALLY REINFORCED SYSTEMS for METAL ROOFS | ARS-2 (M15) | X | | | | | | 5 | NA |
| | | ARS-2 (M20) | X | | | | | | 10 | 5 |
| | | ARS-2 (M25XT) | X | | | | | | 15 | 10 |
| | PARTIALLY REINFORCED SYSTEMS for SINGLE-PLY ROOFS | ARS-2 (SP20XT) | | | | | X | | 5 | 5 |
| ARS-2 (SP30XT) | | | | | | X | | 10 | 10 | |
| ARS-3 | COATING ONLY SYSTEMS | ARS-3 (15) | X | | | | X | X | 5* | NA |
| | | ARS-3 (20) | | X | X | X | | | 5* | NA |
| | | ARS-3 (15MB) | | | X | | | | 5* | NA |

Material warranty - Acrymax will supply sufficient materials to repair leaks caused by normal weathering or will replace materials proven defective.

System warranty requires project acceptance, pre-inspection, final inspection, and applicable warranty fee. Must be applied by Acrymax Approved Applicator.

* Material warranty - ARS-3 Systems are for defective materials only and do not cover leaks.